

3,500 to 7,200 GVWR - Low Deck - Single Axle - Drop Deck



Photo may be shown with options.

500 Series Low Deck Models - Single Axle - Tilt Deck - Drop Deck

| Model Number | 501 | 511 | 531 |
|---------------------------|-------|-------|-------|
| Total GVWR (LBS) | 3,000 | 4,250 | 7,200 |
| Total Axle Capacity (LBS) | 3,500 | 3,500 | 6,000 |
| Payload Capacity (LBS) | 2,100 | 3,500 | 6,000 |
| Standard Deck Width | 76" | 76" | 74" |
| Standard Deck Length | 10' | 10' | 12' |
| Deck Height | 15" | 15" | 17" |
| Deck Width Options | None | None | None |
| Deck Length Options | 12' | 12' | 14' |

FEATURES:

- Solid 2" White Oak Deck Floor - Select Models - Durable and Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders - Strength and Long Life
- Dexter Heavy Duty Drop Axles - EZ Lube Grease Hubs - Forward Self-Adjusting Brakes - Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Heavy Duty, Easy to Use, Secure Latch Mechanism for Quick Release
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

| Capacity Features | 501 | 511 | 531 |
|--|----------------------------------|--------------|-----------------------|
| GVWR - Lbs | 3,000 | 4,250 | 7,200 |
| Total Axle Capacity -Lbs | 3,500 | 3,500 | 6,000 |
| Payload Capacity | 2,100 | 3,500 | 6,000 |
| Deck Features | 501 | 511 | 531 |
| Standard Deck Width | 76" x 10' Tilt | | 74" x 12' Tilt |
| Standard Deck Length | 10' | | 12' |
| Standard Deck Height | 15" | | 16" |
| Overall Width | 99" | 99" | 97" |
| Overall Length | 14' | | 16' |
| Deck Width Options | None | | |
| Deck Length Options | 12' | 12' | 14' |
| Deck Flooring Material | 2" Pressure Treated Pine | | 2" Oak Deck |
| Axle & Brake Features | 501 | 511 | 531 |
| Axle Size (LBS) | 3,500 | | 6,000 |
| Dexter Heavy Duty Axle Type | Single 4" Drop Axle | | |
| Slipper Spring Suspension | Yes- Multi Leaf | | |
| Axle Equalizers | No | | |
| Forward Self Adjusting Brakes | None | Yes | Yes |
| EZ Lube Grease Hubs | Yes | | |
| Wheel & Tire Features | 501 | 511 | 531 |
| Radial Tires | ST205/75R15 (C) | | ST235/80R16 (E) |
| Tire Plies | 6 Ply | | 10 Ply |
| Disc Type Wheels | 5-Bolt | | 8-Bolt |
| Wheel Style | White Spoke | | Grey |
| All Wheel Electric Brakes | None | 10" x 2 1/4" | 12" X 2" |
| Trailer Steel Construction Features | 501 | 511 | 531 |
| Steel Frame Construction | 4"x 3" x 1/4" | | 5" x 3" x 1/4" |
| Tongue Construction | 3" Channel | | 4" x 5.4# |
| Crossmember Size | 3" x 2" x 3/16" | | 3" x 4.1# |
| Additional Features | 501 | 511 | 531 |
| Heavy Duty Stake Pockets | 4 | | |
| Ball Hitch | 2" Ball or 2 5/16" or Pintle Eye | | 2 5/16" or Pintle Eye |
| Hitch Height Range | 14" to 18" | | 15" to 19" |
| Drop Leg Jack Rating | 7K Lift - 8K Static | | |
| Diamond Plate Fenders with Full Back Plate | 14 Gauge | | |
| Sealed Beam LED Lighting | All LED Lighting | | |
| Wiring Protection | Steel Conduit | | |
| Wiring Junction Box | None | Yes | |
| Safety Breakaway System | None | Yes | |
| Safety Chain & Hook | Yes | | |

Specifications subject to change without notice.