

8,000 to 15,000 GVWR - Oak Floor - Ultra Low 7 Degree Load Angle



Photo may be shown with options.

4000 Series Tilt Deck Trailer Models - With Ramps - Ultra Low 7 Degree Load Angle

Model Number	4200	4400	4600	4800
Total GVWR (LBS)	8,000	9,990	12,300	15,000
Total Axle Capacity (LBS)	7,000	10,400	12,000	14,000
Payload Capacity (LBS)	5,800	7,200	10,000	16,100
Standard Deck Width	76"	80"	80"	79"
Standard Deck Length	14'	16'	16'	16'
Standard Deck Height	15"	15"	15"	17"
Deck Width Options*	80"	none	none	none
Deck Length Options	16' Tilt	18' Tilt	18' Tilt	18' Tilt

FEATURES:

- Solid 2" White Oak Deck Floor - Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders - Strength and Long Life
- Dexter Heavy Duty Drop Axles - EZ Lube Grease Hubs - Forward Self-Adjusting Brakes - Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

Capacity Features	4200	4400	4600	4800
GVWR - Lbs.	8,000	9,990	12,300	15,000
Total Axle Capacity - Lbs.	7,000	10,400	12,000	14,000
Payload Capacity - Lbs.	5,800	7,200	10,000	16,100
Tilt Deck Features	4200	4400	4600	4800
Standard Deck Width	76"	80"		79"
Standard Deck Length	14'	16'		
Standard Deck Height	15"			17"
Overall Width	98"	102"		
Overall Length	20'	22'		
Deck Width Options	80"	No		
Deck Length Options	14'	18'		
Deck Flooring Material	2" White Oak			
Ultra Low Tilt Deck Design with 4' Ramps	Yes			
Axle & Brake Features	4200	4400	4600	4800
Dexter Heavy Duty Axle Size Lbs.	3,500	5,200	6,000	7,000
Heavy Duty Dexter Axle Type	4" Drop Tandem Axles			
Slipper Spring Suspension	Yes- Multi Leaf			
Load Equalizers	Yes			
EZ Lube Grease Hubs	Yes			
Forward Self Adjusting Brakes	Yes			
All Wheel Electric Brakes	10' x 2 1/4"	12" x 2"		
Tire & Wheel Features	4200	4400	4600	4800
Radial Tires	ST205/75R 15(C)	ST225/75R 15(D)		ST235/80R 16(E)
Tire Plies	6 Ply	8 Ply		10 Ply
Wheel Bolt Pattern	5-Bolt	6-Bolt		8-bolt
Wheel Style	White Spoke			Grey
Trailer Steel Construction Features	4200	4400	4600	4800
Steel Frame Construction	5" x 3" x 3/8" Angle	7" x 4" x 3/8" Angle		7" x 4" x 1/2" Angle
Tongue Construction	4" Channel	5" Channel		6" Channel
Crossmember Size	Structural Channel – 3"x 4.1#			
Ramp Features	4200	4400	4600	4800
Specialized 4' Loading Ramps	Yes			
3lb. Expanded Top of Ramps	Yes			
Knife Edge on Loading Ramp	Yes			
EZ Slide Adjustable Ramp	Adjust from 80" to 6"			
Ramps Lock n Store Vertically	Yes			
Single Handle "Lock & Load" Ramp	Yes			
Additional Features	4200	4400	4600	4800
Heavy Duty 6" Stake Pockets	6	8		
Adjustable Heavy Duty Cast Coupler	Yes			
Adjustable Ball Hitch	2 5/16" Or Adjustable Pintle Eye			
Hitch Height Adjustment Range	15" to 23"			
Step Tongue Length	5'			
Drop Leg Jack Rating	7K Lift – 8K Static			10K Lift – 12K Static
Fender Step	Yes			
Diamond Plate Fender w Full Back Plate	Yes			
Sealed Beam LED Lighting	All LED Lighting			
Wiring Protection Inside Steel Conduit	Yes			
Wiring Junction Box	Yes			
Safety Breakaway System	Yes			
Safety Chains with Hooks	Yes			

Specifications subject to change without notice.