

18,900 GVWR - Extra Wide Series - Tandem Axles - Loading Ramps



Photo may be shown with options.

2960 Extra Wide Series Trailer Models - Tandem Axles - Drop Deck	
Model Number	2960
Total GVWR (LBS)	18,900
Total Axle Capacity (LBS)	16,000
Payload Capacity (LBS)	15,000
Standard Trailer Deck Size	82" x 18'
Deck Height	23"
Deck Width Options	None
Deck Length Options	20' x 22'

FEATURES:

- Solid 2" White Oak Deck Floor – Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders – Strength and Long Life
- Dexter Heavy Duty Drop Axles – EZ Lube Grease Hubs – Forward Self-Adjusting Brakes – Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Rugged “No Bend – No Sag” Loading Ramps for Long Life
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

Capacity Features	2960
GVWR - Lbs.	18,900
Total Axle Capacity	16,000
Payload Capacity	15,000
Deck Features	2960
Standard Deck Width	82"
Standard Deck Length	18'
Standard Deck Height	23"
Overall Width	102"
Overall Length	23'
Deck Width Options	None
Deck Length Options	20' or 22'
Deck Flooring Material	2" White Oak
Axle & Brake Features	2960
Dexter Heavy Duty Axle Size Lbs	8,000
Dexter Heavy Duty Axle Type	Tandem 4" Drop Axles
Slipper Spring Suspension	Yes - Multi Leaf
Load Equalizers	Yes
EZ Lube Grease Hubs	Yes
Forward Self Adjusting Brakes	Yes
All Wheel Electric Brakes	12 1/4 x 3 3/8"
Wheel & Tire Features	2960
Radial Tires	215/75R17.5 (H)
Tire Plies	16 Ply
Disc Type Wheels	8-Bolt
Number Tires	4
Wheel Style	Mod. Silver
Trailer Steel Construction Features	2960
Steel Frame Construction	WF I-Beam 8" x 13#
Tongue Construction	WF I-Beam 8" x 13#
Crossmember Size	Structural Channel 3" x 4.1#
Trailer Ramp Features	2960
FoldUp Heavy Duty Ramps	6 Feet
Ramp Width	19"
EZ Slide Adjustable Ramp	Adjust from 80" to 6"
Ramps Lock n Store In Upright Position	Yes
Ramp Lock System	Flat Bar Pin
Additional Features	2960
Heavy Duty D-Rings	8
Adjustable Coupler	4 Bolt Pintle Eye or Optional 2 ⁵ / ₁₆ Ball Coupler
Hitch Height Range	19" to 27"
Drop Leg Jack Rating	10K Lift - 12K Static
Diamond Plate Fender with Backs	14 Gauge
Step Tongue Design	Straight
Sealed Beam LED Lighting	All LED Lighting
Wiring Protection	Steel Conduit
Wiring Junction Box	Yes
Safety Breakaway System	Yes
Safety Chains with Hooks	Yes

Specifications Subject To Change Without Notice

Cronkhite Trailers | 2212 Kickapoo Dr., Danville, IL 61822 | Phone: 217-443-3700 | Fax: 217-443-3778 | www.cronkhitrailers.com

rev04132019