

22,500 to 47,000 GVWR - Oak Floor - Deck Over - Tandem Axle



Photo may be shown with options.

6000 SERIES DECK OVER TRAILER MODELS - DUAL TANDEM								
Model Number	6000	6100	6110	6200	6210	6300	6310	6400
Total GVWR (LBS)	22,500	25,500	25,500	29,800	29,800	37,000	37,000	47,000
Total Axle Capacity (LBS)	18,000	20,000	20,000	24,000	24,000	30,000	30,000	40,000
Payload Capacity (LBS)	18,000	20,000	20,000	24,000	24,000	30,000	30,000	40,000
Standard Deck Width	96"	96"	96"	96"	96"	96"	96"	96"
Standard Deck Length	18'+5' BT	18'+5' BT	18'+5' BT	18'+5' BT	18'+5' BT	18'+5' BT	18'+5' BT	18'+5' BT
Deck Height	34"	34"	34"	35"	35"	36"	36"	36"
Deck Width Options	102"	102"	102"	102"	102"	102"	102"	102"
Deck Length Options	20' & 22'	20' & 22'	20' & 22'	20' & 22'	20' & 22'	20' & 22'	20' & 22'	20' & 22'
Brake Type	Electric	Electric	Air	Electric	Air	Electric	Air	Air

FEATURES:

- Heavy Duty Dexter Axles
- Upgraded Dexter E-Z Lube™ System
- Upgraded Dexter Forward Self Adjusting Brake™ System
- Strong Slipper Spring Suspension & Equalizer System
- Solid Oak Deck Floors Not Pressure Treated Pine
- I-Beam Frame Construction
- Trailer Electrical Wiring System
- Integrated Tongue Design





FEATURES & SPECIFICATIONS

Capacity Features	6000	6100	6110	6200	6210	6300	6310	6400
GVWR - Lbs.	22,500	25,500	25,500	29,800	29,800	37,000	37,000	47,000
Total Axle Capacity - Lbs.	18,000	20,000	20,000	24,000	24,000	30,000	30,000	40,000
Payload Capacity Lbs.	18,000	20,000	20,000	24,000	24,000	30,000	30,000	40,000
Deck Features	6000	6100	6110	6200	6210	6300	6310	6400
Standard Deck Width	96"							
Standard Deck Length	18' + 5'BT							
Deck Height	34"	34"	34"	35"	35"	36"	36"	36"
Deck Width Options	102"							
Deck Length Options	20' & 22'							
Deck Flooring Material	2" White Oak							
Axle & Brake Features	6000	6100	6110	6200	6210	6300	6310	6400
Dexter Heavy Duty Axle Lbs.	9,000	10,000	10,000	12,000	12,000	15,000	15,000	22,000
Slipper Spring Suspension	Yes							
Load Equalizers	Yes							
Oil Bath Hubs & Bearings	Yes							
Forward Self Adjusting Brakes	Yes							
All Wheel Electric Brakes	Electric	Electric	Air	Electric	Air	Electric	Air	Air
Optional Brakes	Hydraulic (Contact Factory)							None
Tire & Wheel Features	6000	6100	6110	6200	6210	6300	6310	6400
Radial Tire Size	ST235/80R 16				215/75R17.5			
Tires Load Range	E				H			
Tire Plies	10				16			
Wheel Bolt Pattern	8-bolt				8-275mm		10-bolt	
Wheel Style	Dual - Grey				Dual - White			
Trailer Steel Construction Features	6000	6100	6110	6200	6210	6300	6310	6400
Steel Frame Construction	10"@15 Lb.	10"@17 Lb.	10"@15 Lb.	10"@17 Lb.		10"@26Lb.		12"@22 Lb.
Tongue Construction	10"@15 Lb.	10"@17 Lb.	10"@15 Lb.	10"@17 Lb.		10"@26 Lb.		12"@22 Lb.
Crossmember Size	3"@ 4.1 Lb. Channel				4"@ 5.4 Lb. Channel			
Side Rails	6"@ 8.2 Lb. Channel				8"C @ 11.5 Lb.Channel			
Trailer Ramp Features	6000	6100	6110	6200	6210	6300	6310	6400
Fold Up Heavy Duty 5' Ramps	Yes							
Spring Assist Ramps	Yes							
EZ Slide Adjustable Ramp	96" - 26"							
Ramp Width	19"							
Additional Features	6000	6100	6100	6200	6210	6300	6310	6400
Heavy Duty Tie Downs	10							
Adjustable Heavy Duty Cast Coupler	2½" ID 4 Bolt Pintle					3" ID 4 Bolt Pintle		
Height Adjustment Range	18" to 32" (4½" Increments)							
Tongue Length	5'							
Drop Leg Jack Rating	10,000 Lb. Sidewind							
Sealed Beam LED Lighting	Yes							
Wiring Protection Inside Steel Conduit	Yes							
Wiring Junction Box	Yes							
Safety Breakaway System	Yes - All air brake trailers 1 Axle ABS							
Safety Chains with Hooks	Yes							

Specifications Subject To Change Without Notice