500 Series

3,000 to 7,200 GVWR - Low Deck - Single Axle - Drop Deck



500 Series Low Deck Models - Single Axle - Tilt Deck - Drop Deck					
Model Number	501	511	531		
Total GVWR (LBS)	3,000	4,250	7,200		
Total Axle Capacity (LBS)	3,500	3,500	6,000		
Payload Capacity (LBS)	2,100	3,500	6,000		
Standard Deck Width	76"	76"	74"		
Standard Deck Length	10'	10'	12'		
Deck Height	15"	15"	17"		
Deck Width Options	None	None	None		
Deck Length Options	12'	12'	14'		

FEATURES:

- Solid 2" White Oak Deck Floor Select Models Durable and Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders Strength and Long Life
- Dexter Heavy Duty Drop Axles EZ Lube Grease Hubs Forward Self-Adjusting Brakes - Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Heavy Duty, Easy to Use, Secure Latch Mechanism for Quick Release
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





Grankhile Heavy Duty Equipment Trailers

Rugged

Heavy Duty

Dependable

Gronkhite FEATURES & SPECIFICATIONS

Capacity Features	501	511	531	
GVWR - Lbs	3,000	4,250	7,200	
Total Axle Capacity -Lbs	3,500	3,500	6,000	
Payload Capacity	2,100	3,500	6,000	
Deck Features	501	511	531	
Standard Deck Width	76" x 10' Tilt		74" x 12' Tilt	
Standard Deck Length	10'		12'	
Standard Deck Height	15"		16"	
Overall Width	99"	99"	97"	
Overall Length	14'		16'	
Deck Width Options		None		
Deck Length Options	12'	12'	14'	
Deck Flooring Material	2" Pressure Treated Pine		2" Oak Deck	
Axle & Brake Features	501	511	531	
Axle Size (LBS)	3,5	500	6,000	
Dexter Heavy Duty Axle Type	Single 4" Drop Axle			
Slipper Spring Suspension	Yes- Multi Leaf			
Axle Equalizers				
Forward Self Adusting Brakes	None	Yes	Yes	
EZ Lube Grease Hubs	Yes			
Wheel & Tire Features	501	511	531	
Radial Tires	ST205/75R15 (C)		ST235/80R16 (E)	
Tire Plies	6 Ply		10 Ply	
Disc Type Wheels	5-Bolt		8-Bolt	
Wheel Style	White Spoke		Grey	
All Wheel Electric Brakes	None	10" x 2 1/4"	12" X 2"	
Trailer Steel Construction Features	501	511	531	
Steel Frame Construction	4"x 3" x 1/4"		5" x 3" x 1/4"	
Tongue Construction	3" Channel		4" x 5.4#	
Crossmember Size	3" x 2" x 3/16"		3" x 4.1#	
Additional Features	501	511	531	
Heavy Duty Stake Pockets		4		
Ball Hitch	2" Ball or 2 5/16" or Pintle Eye		2 5/16" or Pintle Eye	
Hitch Height Range	14" to 18"		15" to 19"	
Drop Leg Jack Rating		7K Lift - 8K Static		
Diamond Plate Fenders with Full Back Plate	14 Gauge			
Cooled Boom LED Lighting	All LED Lighting			
Sealed Beam LED Lighting		Steel Conduit		
Wiring Protection		Steel Conduit		
	None		es	
Wiring Protection	None None	Ye	es es	

Specifications subject to change without notice.