

Pan Design - 8,700 to 16,100 GVWR - Oak Floor - Drop Axle - Angle Frame



Photo may be shown with options.

2000 SERIES DROP DECK TRAILER MODELS - TANDEM AXLE - LOADING RAMPS

Model Number	2200	2400	2609	2612	2614	2616HD	2900
Total GVWR (LBS)	8,000	9,990	9,990	12,300	13,800	16,100	16,100
Total Axle Capacity (LBS)	7,000	10,400	12,000	12,000	12,000	14,000	14,000
Payload Capacity (LBS)	5,800	7,300	7,200	10,000	11,000	13,000	13,000
Standard Deck Size	76" x 14'	80" x 16'	80" x 16'	80" x 16'	80"x16'	80"x16'	79" x 18'
Deck Height	15"	15"	16"	16"	16"	17"	17"
Deck Width Options*	80"	82" Straight Axle	82" Straight Axle	82" Straight Axle	82" Straight Axle	81" Straight Axle	81" Straight Axle

FEATURES:

- Solid 2" White Oak Deck Floor – Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders – Strength and Long Life
- Heavy Duty Drop Axles – U Lube Grease Hubs – Forward Self-Adjusting Brakes – Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Rugged “No Bend – No Sag” Loading Ramps for Long Life
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

Capacity Features	2200	2400	2609	2612	2614	2616HD	2900
GVWR - Lbs.	8,000	9,990	9,990	12,300	13,800	16,100	16,100
Total Axle Capacity Lbs.	7,000	10,400	12,000	12,000	12,000	14,000	14,000
Payload Capacity Lbs.	5,800	7,300	7,200	10,000	11,000	13,000	13,000
Deck Features	2200	2400	2609	2612	2614	2616HD	2900
Standard Deck Width	76"				80"		
Standard Deck Length	14'				16'	18'	
Standard Deck Height	15"		16"			17"	
Overall Width	96"	102"					
Overall Length	18'	20'				24'	
Deck Width Options	80"	82" w/ Straight Axle				81" w/ Straight Axle	
Deck Length Options	16'	18' - 20'				20' -22'	
Deck Flooring Material	2" White Oak						
Axle & Brake Features	2200	2400	2609	2612	2614	2616HD	2900
Heavy Duty Axle Size Lbs.	3,500	5,200	6,000			7,000	
Heavy Duty Axle Type	4" Drop Tandem Axles						
Slipper Spring Suspension	Yes- Multi Leaf						
Load Equalizers	Yes						
U Lube Grease Hubs	Yes						
Forward Self Adjusting Brakes	Yes						
All Wheel Electric Brakes	10" x 2 1/4"	12" x 2"					
Tire & Wheel Features	2200	2400	2609	2612	2614	2616HD	2900
Radial Tires	ST205/75R 15(D)	ST225/75R 15(D)	ST235/80R 16(E)				
Tire Plies	6 Ply	8 Ply	10 Ply				
Wheel Bolt Pattern	5-Bolt	6-Bolt	8-bolt				
Wheel Style	White Spoke			Grey			
Trailer Steel Construction Features	2200	2400	2609	2612	2614	2616HD	2900
Steel Frame Construction	5"x3"x3/8"	7" x 4" x 3/8" Angle					
Tongue Construction	4" Channel	5" Channel				6" Channel	
Crossmember Size	Structural Channel – 3" x 4.1#						
Ramp Features	2200	2400	2609	2612	2614	2616HD	2900
Stand Up Heavy Duty 4' Ramps	Yes						
EZ Slide Adjustable Ramp	76" to 6"	Adjust from 80" to 6"					
Single Handle "Lock & Load" Ramp Vertical	Yes						
Additional Features	2200	2400	2609	2612	2614	2616HD	2900
Heavy Duty 6" Stake Pockets	4	6				8	
Step Tongue Length				4'	6'		
Adjustable Heavy Duty Cast Coupler	Yes						
Adjustable Ball Hitch	2 5/16" Or Adjustable Pintle Eye						
Hitch Height Adjustment Range	14" to 22"						
Drop Leg Jack Rating	7K Lift – 8K Static						
Fender Step	Yes						
Diamond Plate Fender with Back	14 Gauge						
Sealed Beam LED Lighting	All LED Lighting						
Wiring Protection Inside Steel Conduit	Yes						
Wiring Junction Box	Yes						
Safety Breakaway System	Yes						
Safety Chain & Hooks	Yes						

Specifications subject to change without notice.