

Flush Deck Design - 12,300 to 15,000 GVWR - Oak Floor - Channel Frame



Photo may be shown with options.

50 Extra Wide Series Trailer Models - Flush Deck

Model Number	2650	2950	2950HD
Total GVWR (LBS)	12,300	15,000	18,200
Total Axle Capacity (LBS)	12,000	14,000	16,000
Payload Capacity (LBS)	10,000	12,000	14,500
Standard Deck Width	82"	83"	83"
Standard Deck Length	16' + 2'BT	18'+2'BT	18'+ 2'BT
Deck Height	24"	24"	24"
Deck Length Options	18' & 20'	20' & 22'	20' & 22'

FEATURES:

- Solid 2" White Oak Deck Floor - Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders - Strength and Long Life
- Heavy Duty Drop Axles - U-Lube Grease Hubs - Forward Self-Adjusting Brakes - Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- Rugged "No Bend - No Sag" Loading Ramps for Long Life
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





FEATURES & SPECIFICATIONS

Capacity Features	2650	2950	2950HD
GVWR - Lbs.	12,300	15,000	18,200
Total Axle Capacity - Lbs	12,000	14,000	16,000
Payload Capacity Lbs.	10,000	12,000	14,500
Deck Features	2650	2950	2950HD
Standard Deck Width	82"	83"	
Standard Deck Length	16' + 2'BT	18' + 2'BT	
Standard Deck Height	24"	24"	
Overall Width	102"	102"	
Overall Length	22'	26'	
Deck Width Options	No	No	
Deck Length Options	18' & 20'	20' & 22'	
Deck Flooring Material	2" White Oak		
Axle & Brake Features	2650	2950	2950HD
Heavy Duty Axle Size Lbs.	6,000	7,000	8,000
Heavy Duty Axle Type	Straight Tandem Axles		
Slipper Spring Suspension	Yes - Multi Leaf		
Load Equalizers	Yes		
U-Lube Grease Hubs	Yes		
Forward Self Adjusting Brakes	Yes		
All Wheel Electric Brakes	12" x 2"		
Wheel & Tire Features	2650	2950	2950HD
Radial Tires	ST225/75R 15 (D)	ST215/75R17.5 (H)	
Tire Plies	8 Ply	16 Ply	
Disc Type Wheels	6-Bolt	8-bolt	
Wheel Style	White Spoke	Grey Spoke	
Trailer Steel Construction Features	2650	2950	2950HD
Steel Frame Construction	5" C x 6.7	6"C x 10.5	
Tongue Construction	6" Channel	6" x 10.5	
Crossmember Size	Structural Channel - 3" x 4.1#		
Trailer Ramp Features	2650	2950	2950HD
FoldUp Heavy Duty Ramps	5'		
Ramp Width	14"		
EZ Slide Adjustable Ramp	Adjust from 80" to 6"		
Ramps Lock n Store In Upright Position	Yes		
Ramp Lock System	Flat Bar Pin		
Additional Features	2650	2950	2950HD
Heavy Duty Stake Pockets	6	8	
Adjustable Coupler	Heavy Duty		
Ball Hitch	2 5/16" Or Adjustable Pintle Eye		
Hitch Height Range	19" to 27"		
Drop Leg Jack Rating	7K Lift-8K Static	10K Lift-12K Static	
Diamond Plate Fenders with Backs	14 Gauge		
Step Tongue Design	Yes		
Sealed Beam LED Lighting	All LED lighting		
Wiring Protection	Steel Conduit		
Wiring Junction Box	Yes		
Safety Breakaway System	Yes		
Safety Chains and Hooks	Yes		

Specifications subject to change without notice.